

Betoniteräkset/Reinforcing bars  
Eräkohtaiset sertifikaatit/Certificates for batches  
Updated 2017-11-24

| <b>Lupanro</b>    | <b>Luvanhaltija</b>    | <b>Tuote</b>           | <b>Tunnus</b> | <b>Nimellis-<br/>halkaisija</b> | <b>Tarkastuserän nro</b> |
|-------------------|------------------------|------------------------|---------------|---------------------------------|--------------------------|
| <u>2017-11-24</u> |                        |                        |               |                                 |                          |
| 459               | Celsa Steel Service Oy | Spooled Coils<br>B500B | "1/17"        | 12,0 mm                         | 12/HO 541868             |
| 458               | Celsa Steel Service Oy | Spooled Coils<br>B500B | "1/17"        | 12,0 mm                         | 12/HO 541867             |
| 457               | Celsa Steel Service Oy | Spooled Coils<br>B500B | "1/17"        | 12,0 mm                         | 12/HO 541866             |
| 456               | Celsa Steel Service Oy | Spooled Coils<br>B500B | "1/17"        | 12,0 mm                         | 12/HO 541865             |
| 455               | Celsa Steel Service Oy | Spooled Coils<br>B500B | "1/17"        | 12,0 mm                         | 12/HO 541864             |
| <u>2017-10-16</u> |                        |                        |               |                                 |                          |
| 454               | Celsa Steel Service Oy | Spooled Coils<br>B500B | "1/17"        | 10,0 mm                         | 10/HO 540522             |
| 453               | Celsa Steel Service Oy | Spooled Coils<br>B500B | "1/17"        | 10,0 mm                         | 10/HO 540521             |
| 452               | Celsa Steel Service Oy | Spooled Coils<br>B500B | "1/17"        | 10,0 mm                         | 10/HO 540520             |
| <u>2017-08-25</u> |                        |                        |               |                                 |                          |
| 451               | Celsa Steel Service Oy | Spooled Coils<br>B500B | "1/17"        | 12,0 mm                         | 12/HO 539800             |
| 450               | Celsa Steel Service Oy | Spooled Coils<br>B500B | "1/17"        | 12,0 mm                         | 12/HO 539755             |
| 449               | Celsa Steel Service Oy | Spooled Coils<br>B500B | "1/17"        | 12,0 mm                         | 12/HO 539751             |

2017-06-26

|     |                        |                        |        |         |              |
|-----|------------------------|------------------------|--------|---------|--------------|
| 448 | Celsa Steel Service Oy | Spoiled Coils<br>B500B | "1/17" | 12,0 mm | 12/HO 539039 |
| 447 | Celsa Steel Service Oy | Spoiled Coils<br>B500B | "1/17" | 12,0 mm | 12/HO 539041 |

2017-05-02

|     |                        |   |        |         |              |
|-----|------------------------|---|--------|---------|--------------|
| 446 | Celsa Steel Service Oy | Hot rolled<br>ribbed reinforcing coils<br>B500B | "1/18" | 12,0 mm | 12/NV 114424 |
| 445 | Celsa Steel Service Oy | Hot rolled<br>ribbed reinforcing coils<br>B500B | "1/18" | 12,0 mm | 12/NV 114422 |
| 444 | Celsa Steel Service Oy | Hot rolled<br>ribbed reinforcing coils<br>B500B | "1/18" | 10,0 mm | 12/NV 114251 |

2017-03-14

|     |                        |                        |        |         |              |
|-----|------------------------|------------------------|--------|---------|--------------|
| 443 | Celsa Steel Service Oy | Spoiled Coils<br>B500B | "1/17" | 12,0 mm | 12/HO 536415 |
| 442 | Celsa Steel Service Oy | Spoiled Coils<br>B500B | "1/17" | 12,0 mm | 12/HO 536414 |

2017-03-02

|     |                        |                        |        |         |              |
|-----|------------------------|------------------------|--------|---------|--------------|
| 441 | Celsa Steel Service Oy | Spoiled Coils<br>B500B | "1/17" | 12,0 mm | 12/HO 536413 |
|-----|------------------------|------------------------|--------|---------|--------------|

| Lupanro           | Luvanhaltija      | Tuote  | Tunnus | Nimellis-<br>halkaisija | Tarkastuserän nro    |
|-------------------|-------------------|--|--------|-------------------------|----------------------|
| <u>2003-03-07</u> |                   |  |        |                         |                      |
| 270 E             | WDI Baustahl GmbH | Kylmämuokatut<br>hitsatut raudoitteet<br>B500K / FL 20 | 8 + 6  | 8/8 - 200               | 56000195 - 65 - 2/13 |
| 271 E             | "                 | "  | 8 + 6  | 8/8 - 200               | 56000195 - 65 - 6/13 |

|                   |                        |   |           |           |                      |
|-------------------|------------------------|---|-----------|-----------|----------------------|
| 272 E             | "                      | "   | 8 + 6     | 8/8 - 200 | 56000195 - 65 - 2/13 |
| <u>2003-04-01</u> |                        |   |           |           |                      |
| 273 E             | "                      | "   | 8 + 6     | 8/8 - 150 | 56000195 - 64 - 1/5  |
| 274 E             | "                      | "   | 8 + 6     | 8/8 - 150 | 56000195 - 64 - 2/5  |
| 275 E             | "                      | "   | 8 + 6     | 8/8 - 150 | 56000195 - 64 - 3/5  |
| 276 E             | "                      | "   | 8 + 6     | 8/8 - 150 | 56000195 - 64 - 4/5  |
| <u>2004-09-09</u> |                        |   |           |           |                      |
| 277 E             | A/S Liepajas Metalurģs | Hot rolled ribbed<br>reinforcing bars<br>A500HW | 8 + 6     | 25 mm     | 25/410769            |
| 278 E             | "                      | "   | 8 + 6     | 25 mm     | 25/410785            |
| 279 E             | "                      | "   | 8 + 6     | 25 mm     | 25/410787            |
| 280 E             | "                      | "   | 8 + 6     | 25 mm     | 25/420697            |
| 281 E             | "                      | "   | 8 + 6     | 25 mm     | 25/430728            |
| 282 E             | "                      | "   | 8 + 6     | 25 mm     | 25/430748            |
| 283 E             | "                      | "   | 8 + 6     | 32 mm     | 32/410785            |
| 284 E             | "                      | "   | 8 + 6     | 32 mm     | 32/410787            |
| 285 E             | "                      | "   | 8 + 6     | 32 mm     | 32/410815            |
| 286 E             | "                      | "   | 8 + 6     | 32 mm     | 32/420697            |
| 287 E             | "                      | "   | 8 + 6     | 32 mm     | 32/430728            |
| 288 E             | "                      | "   | 8 + 6     | 32 mm     | 32/430748            |
| <u>2005-03-22</u> |                        |   |           |           |                      |
| 289 E             | Celsa Huta Ostrowiec   | Hot rolled ribbed<br>reinforcing bars<br>A500HW | 8 + 1 + 6 | 10 mm     | 10/44331             |
| 290 E             | "                      | "   | 8 + 1 + 6 | 12 mm     | 12/45867             |
| 291 E             | "                      | "   | 8 + 1 + 6 | 16 mm     | 16/45734             |
| 292 E             | "                      | "   | 8 + 1 + 6 | 20 mm     | 20/46315             |
| 293 E             | "                      | "   | 8 + 1 + 6 | 25 mm     | 25/46302             |
| 294 E             | "                      | "   | 8 + 1 + 6 | 32 mm     | 32/44544             |
| 295 E             | Celsa Huta Ostrowiec   | Hot rolled ribbed<br>reinforcing bars<br>A500HW | 8 + 1 + 6 | 10 mm     | 10/46484             |
| 296 E             | "                      | "   | 8 + 1 + 6 | 12 mm     | 12/46574             |
| 297 E             | "                      | "   | 8 + 1 + 6 | 16 mm     | 16/46662             |
| 298 E             | "                      | "   | 8 + 1 + 6 | 20 mm     | 20/46637             |
| 299 E             | "                      | "   | 8 + 1 + 6 | 25 mm     | 25/46780             |
| 300 E             | "                      | "   | 8 + 1 + 6 | 32 mm     | 32/44554             |

2005-04-19

|       |                      |   |           |       |          |
|-------|----------------------|---|-----------|-------|----------|
| 301 E | Celsa Huta Ostrowiec | Hot rolled ribbed<br>reinforcing bars<br>A500HW | 8 + 1 + 6 | 10 mm | 10/46961 |
| 302 E | "                    | "   | 8 + 1 + 6 | 12 mm | 12/47239 |
| 303 E | "                    | "   | 8 + 1 + 6 | 16 mm | 16/47135 |
| 304 E | "                    | "   | 8 + 1 + 6 | 20 mm | 20/47185 |
| 305 E | "                    | "   | 8 + 1 + 6 | 25 mm | 25/47209 |
| 306 E | "                    | "   | 8 + 1 + 6 | 32 mm | 32/46218 |
| 307 E | "                    | "   | 8 + 1 + 6 | 32 mm | 32/47657 |

2005-05-24

|       |                      |   |           |       |          |
|-------|----------------------|---|-----------|-------|----------|
| 308 E | Celsa Huta Ostrowiec | Hot rolled ribbed<br>reinforcing bars<br>A500HW | 8 + 1 + 6 | 25 mm | 25/47700 |
| 309 E | "                    | "   | 8 + 1 + 6 | 20 mm | 20/47718 |
| 310 E | "                    | "   | 8 + 1 + 6 | 16 mm | 16/47812 |
| 311 E | "                    | "   | 8 + 1 + 6 | 12 mm | 12/47478 |
| 312 E | "                    | "   | 8 + 1 + 6 | 10 mm | 10/47484 |

2005-06-02

|       |                      |   |           |       |          |
|-------|----------------------|---|-----------|-------|----------|
| 313 E | Celsa Huta Ostrowiec | Hot rolled ribbed<br>reinforcing bars<br>A500HW | 8 + 1 + 6 | 32 mm | 32/47650 |
| 314 E | "                    | "   | 8 + 1 + 6 | 25 mm | 25/47702 |
| 315 E | "                    | "   | 8 + 1 + 6 | 20 mm | 20/47751 |
| 316 E | "                    | "   | 8 + 1 + 6 | 16 mm | 16/47810 |
| 317 E | "                    | "   | 8 + 1 + 6 | 12 mm | 12/47987 |
| 318 E | "                    | "   | 8 + 1 + 6 | 10 mm | 10/47770 |
| 319 E | "                    | "   | 8 + 1 + 6 | 10 mm | 10/48368 |

2005-06-21

|       |                      |   |           |       |          |
|-------|----------------------|---|-----------|-------|----------|
| 320 E | Celsa Huta Ostrowiec | Hot rolled ribbed<br>reinforcing bars<br>A500HW | 8 + 1 + 6 | 12 mm | 12/48014 |
| 321 E | "                    | "   | 8 + 1 + 6 | 16 mm | 16/48188 |
| 322 E | "                    | "   | 8 + 1 + 6 | 20 mm | 20/48190 |
| 323 E | "                    | "   | 8 + 1 + 6 | 25 mm | 25/48174 |
| 324 E | "                    | "   | 8 + 1 + 6 | 32 mm | 32/47651 |

2007-06-18

|       |                          |   |       |       |          |
|-------|--------------------------|---|-------|-------|----------|
| 325 E | Helsingin Tukkumyynti Oy | Kuumavalssatut<br>harjatangot<br>A700HW | 9 + 1 | 12 mm | 12/31790 |
| 326 E | "                        | "                                       | 9 + 1 | 12 mm | 12/21477 |
| 327 E | "                        | "                                       | 9 + 1 | 14 mm | 14/31789 |
| 328 E | "                        | "                                       | 9 + 1 | 14 mm | 14/31789 |
| 329 E | "                        | "                                       | 9 + 1 | 16 mm | 16/31790 |
| 330 E | "                        | "                                       | 9 + 1 | 16 mm | 16/31789 |

2007-08-27

|       |                              |  |           |        |                 |
|-------|------------------------------|--|-----------|--------|-----------------|
| 331 E | PPU "ECOSTEEL"<br>Sp. z.o.o. | Welded fabrics<br>B500K/FL20<br>sizes<br>5000/2350,150x150 | 1 + 4 + 9 | 6,0 mm | 6,0/732368      |
| 332 E | "                            | "  | 1 + 4 + 9 | 6,0 mm | 6,0/732368      |
| 333 E | "                            | "  | 1 + 4 + 9 | 6,0 mm | 6,0/732368      |
| 334 E | "                            | "  | 1 + 4 + 9 | 5,0 mm | 5,0/12269/12378 |
| 335 E | "                            | "  | 1 + 4 + 9 | 5,0 mm | 5,0/12269/12378 |
| 336 E | "                            | "  | 1 + 4 + 9 | 5,0 mm | 5,0/12612/12378 |
| 337 E | "                            | "  | 1 + 4 + 9 | 5,0 mm | 5,0/12612/12378 |
| 338 E | "                            | "  | 1 + 4 + 9 | 5,0 mm | 5,0/12612/12375 |
| 339 E | "                            | "  | 1 + 4 + 9 | 8,0 mm | 8,0/12669       |
| 340 E | "                            | "  | 1 + 4 + 9 | 8,0 mm | 8,0/12669       |
| 341 E | "                            | "  | 1 + 4 + 9 | 8,0 mm | 8,0/12669       |

2008-03-11

|       |               |   |       |         |            |
|-------|---------------|---|-------|---------|------------|
| 342 E | ArcelorMittal | Hot rolled ribbed<br>reinforcing bars<br>A500HW | 2 + 9 | 16,0 mm | 16,0/21644 |
| 343 E | "             | "   | 2 + 9 | 16,0 mm | 16,0/21638 |
| 344 E | "             | "   | 2 + 9 | 20,0 mm | 20,0/21125 |
| 345 E | "             | "   | 2 + 9 | 20,0 mm | 20,0/21133 |

2008-03-18

|       |                                    |  |      |         |             |
|-------|------------------------------------|--|------|---------|-------------|
| 346 E | Zakłady Wyrobów<br>Metalowych S.A. | Cold worked ribbed<br>welded fabrics<br>B500K/FL20 | 9/25 | 5,0 mm  | 5,0/730908  |
| 347 E | "                                  | "  | "    | 6,0 mm  | 6,0/733362  |
| 348 E | "                                  | "  | "    | 8,0 mm  | 8,0/733046  |
| 349 E | "                                  | "  | "    | 10,0 mm | 10,0/722770 |
| 350 E | "                                  | "  | "    | 5,0 mm  | 5,0/733357  |
| 351 E | "                                  | "  | "    | 6,0 mm  | 6,0/733358  |

|       |   |   |   |         |             |
|-------|---|---|---|---------|-------------|
| 352 E | " | " | " | 8,0 mm  | 8,0/433041  |
| 353 E | " | " | " | 10,0 mm | 10,0/722770 |
| 354 E | " | " | " | 5,0 mm  | 5,0/729013  |
| 355 E | " | " | " | 6,0 mm  | 6,0/733357  |
| 356 E | " | " | " | 8,0 mm  | 8,0/723018  |
| 357 E | " | " | " | 10,0 mm | 10,0/723686 |
| 358 E | " | " | " | 5,0 mm  | 5,0/722455  |
| 359 E | " | " | " | 6,0 mm  | 6,0/723003  |
| 360 E | " | " | " | 10,0 mm | 10,0/423491 |
| 361 E | " | " | " | 8,0 mm  | 8,0/57742   |
| 362 E | " | " | " | 5,0 mm  | 5,0/57253   |
| 363 E | " | " | " | 6,0 mm  | 6,0/56940   |
| 364 E | " | " | " | 8,0 mm  | 8,0/57771   |
| 365 E | " | " | " | 10,0 mm | 10,0/724702 |
| 366E  | " | " | " | 5,0 mm  | 5,0/53104   |
| 367 E | " | " | " | 6,0 mm  | 6,0/56939   |
| 368 E | " | " | " | 8,0 mm  | 8,0/57740   |
| 369E  | " | " | " | 10,0 mm | 10,0/713956 |

2008-04-11

|     |               |   |       |          |            |
|-----|---------------|---|-------|----------|------------|
| 370 | ArcelorMittal | Hot rolled ribbed<br>reinforcing<br>bars A500HW | 2 + 9 | 16,00 mm | 16,0/23005 |
| 371 | "             | "   | "     | 16,00 mm | 16,0/23007 |
| 372 | "             | "   | "     | 20,0 mm  | 20,0/22269 |
| 373 | "             | "   | "     | 20,0 mm  | 20,0/22696 |
| 374 | "             | "   | "     | 25,0 mm  | 25,0/21438 |
| 375 | "             | "   | "     | 25,0 mm  | 25,0/22596 |
| 376 | "             | "   | "     | 32,0 mm  | 32,0/22219 |
| 377 | "             | "   | "     | 32,0 mm  | 32,0/22238 |

2008-06-09

|     |               |   |       |         |            |
|-----|---------------|---|-------|---------|------------|
| 378 | ArcelorMittal | Hot rolled ribbed<br>reinforcing<br>bars A500HW | 2 + 9 | 32,0 mm | 32,0/23705 |
| 379 | "             | "   | "     | 32,0 mm | 32,0/23769 |
| 380 | "             | "   | "     | 25,0 mm | 25,0/24119 |
| 381 | "             | "   | "     | 25,0 mm | 25,0/20819 |
| 382 | "             | "   | "     | 20,0 mm | 20,0/24326 |
| 383 | "             | "   | "     | 20,0 mm | 20,0/23958 |

|     |   |   |   |         |            |
|-----|---|---|---|---------|------------|
| 384 | " | " | " | 16,0 mm | 16,0/24659 |
| 385 | " | " | " | 16,0 mm | 16,0/24648 |

2008-08-13

|     |               |   |   |         |            |
|-----|---------------|---|---|---------|------------|
| 386 | ArcelorMittal | Hot rolled ribbed reinforcing bars A500HW | " | 25,0 mm | 25,0/25767 |
| 387 | "             | "   | " | 25,0 mm | 25,0/25683 |
| 388 | "             | "   | " | 32,0 mm | 32,0/25464 |
| 389 | "             | "   | " | 32,0 mm | 32,0/24209 |

2009-01-14

|     |  |  |           |        |            |
|-----|--|--|-----------|--------|------------|
| 390 | Fapricela, Indústria de Trefilaria, S.A. | Cold worked welded fabrics B500K / FL 20 | 7 + 3 + 8 | 5,0 mm | 5,0/536742 |
| 391 | "  | "  | 7 + 3 + 8 | 6,0 mm | 6,0/535672 |

2009-06-11

|     |               |   |       |         |            |
|-----|---------------|---|-------|---------|------------|
| 392 | ArcelorMittal | Hot rolled ribbed reinforcing bars A500HW | 2 + 9 | 10,0 mm | 10,0/28463 |
| 393 | "             | "   | "     | 10,0 mm | 10,0/28466 |

2009-07-14

|     |               |   |       |         |            |
|-----|---------------|---|-------|---------|------------|
| 394 | ArcelorMittal | Hot rolled ribbed reinforcing bars A500HW | 2 + 9 | 10,0 mm | 10,0/11067 |
| 395 | "             | "   | "     | 12,0 mm | 12,0/11270 |
| 396 | "             | "   | "     | 12,0 mm | 12,0/11067 |

2009-08-04

|     |  |                                  |           |         |             |
|-----|--|----------------------------------|-----------|---------|-------------|
| 397 | Fapricela, Indústria de Trefilaria, S.A. | Cold worked fabric B500K / FL 20 | 7 + 3 + 8 | 8,0 mm  | 8,0/541609  |
| 398 | "  | "                                | "         | 8,0 mm  | 8,0/536825  |
| 399 | "  | "                                | "         | 8,0 mm  | 8,0/536824  |
| 400 | "  | "                                | "         | 10,0 mm | 10,0/537497 |
| 401 | "  | "                                | "         | 10,0 mm | 10,0/537555 |
| 402 | "  | "                                | "         | 10,0 mm | 10,0/537553 |

2009-10-08

|     |               |   |       |         |            |
|-----|---------------|---|-------|---------|------------|
| 403 | ArcelorMittal | Hot rolled ribbed reinforcing bars A500HW | 2 + 9 | 10,0 mm | 10,0/12199 |
| 404 | "             | "   | "     | 10,0 mm | 10,0/12220 |
| 405 | "             | "   | "     | 12,0 mm | 12,0/12039 |

|     |   |   |   |         |            |
|-----|---|---|---|---------|------------|
| 406 | " | " | " | 12,0 mm | 12,0/12041 |
|-----|---|---|---|---------|------------|

2009-12-01

|     |               |   |       |         |            |
|-----|---------------|---|-------|---------|------------|
| 407 | ArcelorMittal | Hot rolled ribbed reinforcing bars A500HW | 2 + 9 | 10,0 mm | 10,0/13013 |
|-----|---------------|---|-------|---------|------------|

|     |   |   |   |         |            |
|-----|---|---|---|---------|------------|
| 408 | " | " | " | 12,0 mm | 12,0/13324 |
|-----|---|---|---|---------|------------|

|     |   |   |   |         |            |
|-----|---|---|---|---------|------------|
| 409 | " | " | " | 12,0 mm | 12,0/13325 |
|-----|---|---|---|---------|------------|

2009-12-01

|     |  |                                  |           |        |            |
|-----|--|----------------------------------|-----------|--------|------------|
| 410 | Fapricela, Indústria de Trefilaria, S.A. | Cold worked fabric B500K / FL 20 | 7 + 3 + 8 | 6,0 mm | 6,0/291973 |
|-----|--|----------------------------------|-----------|--------|------------|

|     |   |   |   |        |            |
|-----|---|---|---|--------|------------|
| 411 | " | " | " | 6,0 mm | 6,0/291942 |
|-----|---|---|---|--------|------------|

|     |   |   |   |        |            |
|-----|---|---|---|--------|------------|
| 412 | " | " | " | 6,0 mm | 6,0/291941 |
|-----|---|---|---|--------|------------|

|     |   |   |   |        |            |
|-----|---|---|---|--------|------------|
| 413 | " | " | " | 8,0 mm | 8,0/544612 |
|-----|---|---|---|--------|------------|

|     |   |   |   |        |            |
|-----|---|---|---|--------|------------|
| 414 | " | " | " | 8,0 mm | 8,0/544613 |
|-----|---|---|---|--------|------------|

|     |   |   |   |        |            |
|-----|---|---|---|--------|------------|
| 415 | " | " | " | 8,0 mm | 8,0/544774 |
|-----|---|---|---|--------|------------|

|     |   |   |   |         |             |
|-----|---|---|---|---------|-------------|
| 416 | " | " | " | 10,0 mm | 10,0/540055 |
|-----|---|---|---|---------|-------------|

|     |   |   |   |         |             |
|-----|---|---|---|---------|-------------|
| 417 | " | " | " | 10,0 mm | 10,0/540057 |
|-----|---|---|---|---------|-------------|

|     |   |   |   |         |             |
|-----|---|---|---|---------|-------------|
| 418 | " | " | " | 10,0 mm | 10,0/545440 |
|-----|---|---|---|---------|-------------|

2010-01-26

|     |  |                                  |       |        |            |
|-----|--|----------------------------------|-------|--------|------------|
| 419 | Fapricela, Indústria de Trefilaria, S.A. | Cold worked fabric B500K / FL 20 | 7+3+8 | 5,0 mm | 5,0/545642 |
|-----|--|----------------------------------|-------|--------|------------|

|     |   |   |   |   |            |
|-----|---|---|---|---|------------|
| 420 | " | " | " | " | 5,0/545618 |
|-----|---|---|---|---|------------|

|     |   |   |   |   |            |
|-----|---|---|---|---|------------|
| 421 | " | " | " | " | 5,0/545623 |
|-----|---|---|---|---|------------|

|     |   |   |   |   |            |
|-----|---|---|---|---|------------|
| 422 | " | " | " | " | 5,0/545628 |
|-----|---|---|---|---|------------|

|     |   |   |   |        |            |
|-----|---|---|---|--------|------------|
| 423 | " | " | " | 6,0 mm | 6,0/546462 |
|-----|---|---|---|--------|------------|

2010-04-29

|     |                        |                             |     |        |                 |
|-----|------------------------|-----------------------------|-----|--------|-----------------|
| 424 | Celsa Steel Service AB | Welded fabrics B500K / FL20 | 6+2 | 5,0 mm | 5,0/79189/79696 |
|-----|------------------------|-----------------------------|-----|--------|-----------------|

|     |   |   |   |   |                 |
|-----|---|---|---|---|-----------------|
| 425 | " | " | " | " | 5,0/79200/79189 |
|-----|---|---|---|---|-----------------|

|     |   |   |   |        |                 |
|-----|---|---|---|--------|-----------------|
| 426 | " | " | " | 6,0 mm | 6,0/78880/78880 |
|-----|---|---|---|--------|-----------------|

|     |   |   |   |   |                 |
|-----|---|---|---|---|-----------------|
| 427 | " | " | " | " | 6,0/78880/78860 |
|-----|---|---|---|---|-----------------|

|     |   |   |   |        |                 |
|-----|---|---|---|--------|-----------------|
| 428 | " | " | " | 8,0 mm | 8,0/79123/79125 |
|-----|---|---|---|--------|-----------------|

|     |   |   |   |   |                 |
|-----|---|---|---|---|-----------------|
| 429 | " | " | " | " | 8,0/79126/79126 |
|-----|---|---|---|---|-----------------|

|     |   |   |   |   |                 |
|-----|---|---|---|---|-----------------|
| 430 | " | " | " | " | 8,0/79125/79126 |
|-----|---|---|---|---|-----------------|



2011-07-05

|     |              |                                  |      |         |             |
|-----|--------------|----------------------------------|------|---------|-------------|
| 431 | VMT Steel Oy | Kuumavalssatut harjatangot B500B | 1+17 | 16,0 mm | 16/HO492586 |
|-----|--------------|----------------------------------|------|---------|-------------|

2012-08-21

|     |                        |                              |     |         |       |
|-----|------------------------|------------------------------|-----|---------|-------|
| 432 | Celsa Steel Service AB | Welded fabrics B500K / FL 20 | 6+2 | 10,0 mm | 11882 |
|-----|------------------------|------------------------------|-----|---------|-------|

2013-10-29

|     |                    |   |            |                      |          |
|-----|--------------------|---|------------|----------------------|----------|
| 433 | R-Group Finland Oy | Kylmämuokattu ruostumaton harjatanko B600KX | 9/ 5/ 4/ 2 | 5,0 mm<br>pituus 6 m | 5/RX9341 |
|-----|--------------------|---|------------|----------------------|----------|

|     |                    |   |            |                            |          |
|-----|--------------------|---|------------|----------------------------|----------|
| 434 | R-Group Finland Oy | Kylmämuokattu ruostumaton harjatanko B600KX | 9/ 5/ 4/ 2 | 7,0 mm,<br>pituus 6m ja 9m | 7/RX9479 |
|-----|--------------------|---|------------|----------------------------|----------|

|     |                    |   |            |                            |          |
|-----|--------------------|---|------------|----------------------------|----------|
| 435 | R-Group Finland Oy | Kylmämuokattu ruostumaton harjatanko B600KX | 9/ 5/ 4/ 2 | 9,0 mm,<br>pituus 6m ja 9m | 7/RX9364 |
|-----|--------------------|---|------------|----------------------------|----------|

|     |                    |   |            |                             |          |
|-----|--------------------|---|------------|-----------------------------|----------|
| 436 | R-Group Finland Oy | Kylmämuokattu ruostumaton harjatanko B600KX | 9/ 5/ 4/ 2 | 11,0 mm,<br>pituus 6m ja 9m | 7/RX9442 |
|-----|--------------------|---|------------|-----------------------------|----------|

2014-11-07

|     |   |   |       |         |          |
|-----|---|---|-------|---------|----------|
| 437 | FCC Industrial e Infraestructuras Energéticas, S.A.U. | Hot rolled ribbed reinforcing bars B500B (Krybar-165) | "4/9" | 12,0 mm | 12/31740 |
|-----|---|---|-------|---------|----------|

|     |   |   |       |         |          |
|-----|---|---|-------|---------|----------|
| 438 | FCC Industrial e Infraestructuras Energéticas, S.A.U. | Hot rolled ribbed reinforcing bars B500B (Krybar-165) | "4/9" | 12,0 mm | 12/31744 |
|-----|---|---|-------|---------|----------|

|     |   |   |       |         |          |
|-----|---|---|-------|---------|----------|
| 439 | FCC Industrial e Infraestructuras Energéticas, S.A.U. | Hot rolled ribbed reinforcing bars B500B (Krybar-165) | "4/9" | 20,0 mm | 20/31734 |
|-----|---|---|-------|---------|----------|

|     |   |   |       |         |          |
|-----|---|---|-------|---------|----------|
| 440 | FCC Industrial e Infraestructuras Energéticas, S.A.U. | Hot rolled ribbed reinforcing bars B500B (Krybar-165) | "4/9" | 20,0 mm | 20/31744 |
|-----|---|---|-------|---------|----------|